

# **BLANK PAGE**



IS: 11573 - 1986

# Indian Standard

## SPECIFICATION FOR POLYAMIDE YARN FOR CYCLE AND RICKSHAW TYRES

UDC 677:072:6:629:11:012:553:1



© Copyright 1986

INDIAN STANDARDS INSTITUTION
MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG
NEW DELHI 110002

## Indian Standard

## SPECIFICATION FOR POLYAMIDE YARN FOR CYCLE AND RICKSHAW TYRES

#### Industrial Textiles Sectional Committee, TDC 49

Chairman

Representing

SHRI A. CHELLARAJ

Madura Coats Ltd, Madurai

Members

SHRI KANAGARAJ ARTHUR

SHRI BASANT KUMAR SHRI M. L. BEHRANI

SHRI T. CHANDRAMOHAN

SHRI N. MURUGANANDAN ( Alternate ) SHRI B. K. SEN CHAUDHURI

SHRI J. CHATTERJEE SHRI R. M. GHOSH ( Alternate )

SHRI A. N. CHOUDHARY

SHRI K. GOPINATH ( Alternate )

SHRI B. D. DUBEY

Andrew Yule & Co, Kalyani

(Inspection Wing), New Delhi

SHRI A. K. SEHGAL ( Alternate )

SHRI S. R. GANGULI SHRI D. C. SEN ( Alternate )

SHRI M. M. GURBAXANI

DR V. G. KAMATH DR A. R. MUKHERJEE ( Alternate )

SHRI PULIN L. KINARIWALA SHRI S. G. JAMBHEKAR ( Alternate )

SHRI R. LAKSHMINARYANAN SHRI K. S. LOGANATHAN

SHRI A. SIRCAR ( Alternate ) DR A. S. NAIR

SHRI S. G. PAL

SHRI S. D. ROY ( Alternate )

Shri B. Roy SHRI R. I. MIDHA, Director ( Tex )

Shriram Fibres Ltd, Madras Basant Pran Electric Co Pvt Ltd, Calcutta

Ministry of Defence (R & D) Simplex Mills Co Ltd, Bombay

Escon Consultants Pvt Ltd, Calcutta

Jaya Shree Textiles & Industries, Rishra

Directorate General of Supplies & Disposals

Goodyear India Limited, Calcutta

Century Rayon, Thane

Nirlon Synthetic Fibres & Chemicals Ltd, Bombay

Cosmos India Rubber Works Private Ltd, Bombay

Fenner (India) Ltd, Madurai Dunlop India Ltd, Sahaganj

Premier Tyres Ltd, Bombay Tyre Corporation of India Ltd, Calcutta

Techno Polymer Laboratories, Calcutta . Director General, ISI ( Ex-officio Member )

Secretary SHRI A. R. BANERJEE Joint Director ( Tex ), ISI

(Continued on page 2)

#### © Copyright 1986

#### INDIAN STANDARDS INSTITUTION

This publication is protected under the Indian Copyright Act (XIV of 1957) and reproduction in whole or in part by any means except with written permission of the publisher shall be deemed to be an infringement of copyright under the said Act.

#### IS: 11573 - 1986

(Continued from page 1)

#### Tyre Cord Yarn and Warp Sheet Subcommittee, TDC 49:4

Convener

Representing

SHRI K. S. LOGANATHAN

Dunlop India Ltd, Sahagan j

Members

SHRI A. SIRCAR ( Alterante to

Shri K. S. Loganathan )

SHRI U. K. BANERJEE

SHRI P. R. BHATTACHARYA

Goodyear India Ltd, Calcutta Escon Consultants Pvt Ltd, Calcutta

SHRI B. CHAKRAVORTY ( Alternate )

SHRI A. CHELIARAJ SHRI M. R. S. GUPTA

Madura Coats Ltd, Madurai Gokak Mills, Gokak Falls

DR V. G. KAMATH

Nirlon Synthetic Fibres & Chemicals Ltd, Bombay

DR A. R. MUKHERJEE ( Alternate )

SHRI S. KRISHNAMOORTHY SHRI A. R. VERADARAJAN ( Alternate )

Ceat Tyres of India Ltd, Bombay

DR RAMESH KUMAR

J. K. Synthetics Ltd, Kota

SHRI N. K. AGARWAL ( Alternate )

SHRIS. K. MUSTAFI SHRI V. K. MISRA ( Alternate )

Modi Rubber Ltd, Modipuram

SHRI G. R. SHANKARA

MRF Limited, Madras

NARAYANAN

SHRI M. M. PRABHU

DR S. M. SHETTY ( Alternate )

REPRESENTATIVE

Shri Ram Rayons, Kota

National Rayon Corporation Ltd, Bombay

REPRESENTATIVE SHRI S. C. K. SHAH

Ministry of Defence (R & D) Shri Ram Fibres Ltd, Madras

SHRI K. N. RANGANATH ( Alternate )

## Indian Standard

## SPECIFICATION FOR POLYAMIDE YARN FOR CYCLE AND RICKSHAW TYRES

#### O. FOREWORD

- **0.1** This Indian Standard was adopted by the Indian Standards Institution on 10 March 1986, after the draft finalized by the Industrial Textiles Sectional Committee had been approved by the Textile Division Council.
- 0.2 In view of the wide usage of polyamide tyre yarn by the cycle and rickshaw tyre manufacturing industry, an urgent need was felt for formulating an Indian Standard on this subject and keeping this in view the present standard has been prepared. It is hoped that this will help in regulating the quality of polyamide tyre yarns.
- 0.3 For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test or analysis, shall be rounded off in accordance with IS: 2-1960\*. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

#### 1. SCOPE

1.1 This standard prescribes the requirements of polyamide tyre yarn for cycle and rickshaw tyres.

#### 2. TERMINOLOGY

2.1 Tyre Yarn — A yarn used as a structural reinforcement of cycle and rickshaw tyres.

#### 3. MANUFACTURE

3.1 Yarn shall be made out of continuous polyamide filament. The nominal tex (denier) of the polyamide filament used shall be as given in Table 1. The yarn shall be well and evenly twisted and shall be reasonably free from defects, such as knots, slubs and projections that would affect the serviceability of the yarn.

<sup>\*</sup>Rules for rounding off numerical values ( revised ).

## TABLE 1 REQUIREMENTS OF POLYAMIDE TYRE YARN FOR CYCLE AND RICKSHAW TYRE

(Clauses 3.1 and 4.1)

SL No.	CHARACTERISTIC	REQUIREMENT	METHOD OF TEST
(1)	(2)	(3)	(4)
i)	Tex ( denier )	102 (918) $\pm$ 4 percent	IS: 4910 ( Part 1 )- 1968*
ii)	Twist per metre (single ply) Tolerance	200-300 ± 15 for any patticular twist value in the above range	IS : 832-1985†
iii)	Breaking strength Min, N	65	IS: 4910 ( Part 2 )- 1968‡
iv)	a) Elongation at break, percent, Min	16	do
	b) Elongation percent, at 45 N	11.5 ± 1.5 percent	do

NOTE - 1N = 0.102 kgf approximately.

†Methods for determination of twist in yarn ( first revision ).

†Methods of test for tyre yarns, cords and tyre cord fabrics made from man-made fibres: Part 2 Breaking load, elongation at break and tenacity.

#### 4. REQUIREMENTS

4.1 The requirements of polyamide yarn shall be as given in Table 1.

#### 5. MARKING

- 5.1 Each package containing polyamide yarn for cycle and rickshaw tyre shall be accompanied by a label stating the following:
  - a) Name of the material (in code no., if any);
  - b) Manufacturer's name, initials or trade-mark, if any;
  - c) Net mass; and
  - d) Date of manufacture.
- 5.2 Each package of polyamide yarn may also be marked with the ISI Certification Mark.

Note — The use of the ISI Certification Mark is governed by the provisions of the Indian Standards Institution (Certification Marks) Act and the Rules and Regulations made thereunder. The ISI Mark on products covered by an Indian Standard conveys the assurance that they have been produced to comply with the requirements of that standard urder a well-defined system of inspection, testing and quality control which is devised and supervised by ISI and operated by the producer. ISI marked products are also continuously checked by ISI for conformity to that standard as a further safeguard. Details of conditions under which a licence for the use of the ISI Certification Mark may be granted to manufacturers or processors, may be obtained from the Indian Standards Institution.

<sup>\*</sup>Methods of test for tyre yarns, cords and tyre cord fabrics made from man-made fibres: Part 1 Linear density.

#### 6. PACKING

**6.1** The bobbins, cheeses or cones of polyamide yarn for cycle and rickshaw tyre shall be packed in cartons as agreed to between the buyer and the seller.

#### 7. SAMPLING AND CRITERIA FOR CONFORMITY

7.1 The sampling and criteria for conformity of tyre yarn shall be as prescribed in IS: 4910 ( Part 12 )-1981\*.

<sup>\*</sup>Methods of test for tyre yarns, cords and tyre cord fabrics made from man-made fibres: Part 12 Sampling for tyre yarns, cords and tyre cord fabrics made from polyamide.

### INTERNATIONAL SYSTEM OF UNITS (SI UNITS)

### Base Units

QUANTITY	Unit	Symbol		
Length	metre	m		
Mass	kilogram	kg		
Time	second	5		
Electric current	ampere	Α		
Thermodynamic temperature	kelvin	K		
Luminous intensity	candela	cd		
Amount of substance	mole	mol		
Supplementary Units				
QUANTITY	Unit	SYMBOL		
Plane angle	radian	rad		
Solid angle	steradian	sr		
Derived Units				
Quantity	Unit	Symbol		Dı
Force	newton	N	1	N =
Energy	ioule	١	1	τ.

QUANTITY	$\mathbf{U}_{\mathbf{NIT}}$	Symbol	DEFINITION
Force	newton	N	$1  N = 1 \text{ kg.m/s}^{2}$
Energy	joule	J	$J = 1 N_{\bullet}m$
Power	watt	W	1  W = 1 J/s
Flux	weber	Wb	$1 \text{ Wb} = 1 \text{ V}_{\bullet} \text{s}$
Flux density	tesla	T	$1  T = 1 \text{ Wb/m}^s$
Frequency	hertz	Hz	$1 \text{ Hz} = 1 \text{ c/s (s}^{-1})$
Electric conductance	siemens	S	1  S = 1  A/V
Electromotive force	volt	V	1 V = 1 W/A
Pressure, stress	pa <b>scal</b>	Pa	$1 Pa = 1 N/m^3$